

Steel Quad Wagon

Quad Wagon

- 25' long x 8.5' wide x 38" side height
- 3/16" AR200 (100,000 PSI) or 3/16" AR400 (180,000 PSI) or 1/8" Hardox 450 (200,000 PSI) yield strength
- Base model Steel Quad Wagon – 18,000 lbs
- Tub-style body with rounded corners and flat floor

Body

- Sloped ledges, self-cleaning
- DOT reflective tape
- H.D. Tube top rail
- Plank pockets
- Solid seam welding
- Starblasted, epoxy undercoat and urethane top coat (5-year warranty)
- All hinges greasable or greaseless composite bushings
- Fully integrated sealed beam pre-manufactured wiring/lighting harness
- Heavy duty 3/16" or 1/4" trapezoidal western style tipping sills
- Adjustable rear hinge

Frame Specifications

- SAF Holland CBX25 Integrated air suspension and axle
- 25,000 lb. axles and ABS axle comes with unimount wheels
- Sealco CVSS 121 air system
- 16 1/2" x 7" brakes
- High tensile steel I-Beam frame
- Haldex Slack Adjusters
- Starblasted, epoxy undercoat, urethane top coat
- Premier drawbar eye assembly
- DOT reflective tape
- RTAC lengths/specs
- Bulldog tongue jack
- 22.5" tires on white steel rims
- Removable rear impact guard

Available Options

- Mechanical trip, air trip, or hydraulic lift end gate
- Lightweight hubs and drums
- Aluminum rims
- Mid-mount hoist stabilizer
- Crank/chain mesh gravel guard tarp
- Crank/chain neoprene gravel guard tarp
- Electric mesh gravel guard tarp installed
- Electric neoprene gravel guard tarp
- Box liners available
- Turnbuckles and rubber seal for Hazmat gate
- Axle lift systems

